


Product Data Sheet Item No. 203-030

Net by the m² (Custom-Made)

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 819 818
Mail: office@safetynet365.com
Web: www.safetynet365.com



TECHNICAL SPECIFICATIONS

Dimensions:	custom-made width, custom-made length
Available Colors:	black, white
Material:	high tenacity polypropylene, knotless
Material Diameter:	Ø 1.5 mm
Mesh Size:	30 x 30 mm
Pose of Meshes:	quadratic (square)
Mesh Connection:	knotless braid
Edge Design:	reinforced selvage cord of approx. 7 mm
Max. Tensile Strength of a Mesh:	250 N
Certificate:	Oeko-Tex® certificate 12.0.02466
Continuous Operating Temperature:	-40 to +80 °C
Melting Point:	165 °C
Yarn Moisture Regain:	0%
Resistance to Weak/Strong Acids:	very good/good
Resistance to Weak/Strong Alkalis:	good/bad
Resistance to Organic Solvents:	good
Resistance to Benzine and Greases:	very good
Bending Strength & Abrasion Resistance:	good
Weather-Resistance:	good
UV-Resistance:	300 kly
Tensile Strength After Two Years of Climatic Influences:	90%
Customs Tariff No.:	56081930
Weight per Unit Area:	50 g/m ²