

# Product Data Sheet Item No. SN-0166-025

## Luggage Net with Elastic Edge

Schutznetze24 GmbH  
 Weyerberg 5, DE-35614 Aßlar-Berghausen  
 Phone: +49 (0) 6443 - 436 96 40  
 Mail: office@safetynet365.com  
 Web: www.safetynet365.com



### TECHNICAL DATA

<b>Available Colors</b>	black, beige (hemp colored)
<b>Material</b>	polyester, knotless, polyamide screw-on brackets
<b>Material Diameter</b>	Ø 2.5 mm
<b>Mesh Size</b>	25 x 25 mm
<b>Pose of Meshes</b>	rhombic (diamond mesh)
<b>Mesh Connection</b>	knotless braid
<b>Edge Design</b>	adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round
<b>Certificate</b>	Oeko-Tex®; certificate 1904052
<b>Continuous Operating Temperature</b>	-40 to +100 °C
<b>Melting Point</b>	260 °C
<b>Yarn Moisture Regain</b>	0.5 to 2.0%
<b>Tensile Strength Reduction Because Of Moisture</b>	0%
<b>Resistance to Weak/Strong Acids</b>	good/not good
<b>Resistance to Weak/Strong Alkalis</b>	good/good
<b>Resistance to Organic Solvents</b>	good
<b>Resistance to Benzine and Greases</b>	good
<b>Bending Strength &amp; Abrasion Resistance</b>	good
<b>Weather-Resistance</b>	good
<b>Tensile Strength After Two Years of Climatic Influences</b>	90%
<b>Elasticity After Years of Climatic Influences</b>	good long-term flexibility, little elongation
<b>Flexibility When Used in Water</b>	stays flexible
<b>Contraction When Used in Water</b>	low contraction

<b>Contraction When Used Outside</b>	no contraction
<b>Behavior in High Heat / Fire</b>	melting
<b>Included Parts</b>	luggage net, rubber cord, 4 or 5 screw-on brackets (depending on size), fastener for rubber cord, comes with an additional hook for the 1000 mm variant
<b>Customs Tariff No.</b>	56081930
<b>Total Weight</b>	0.00 kg