Product Data Sheet Item No. SN-016606

Luggage Net 300 x 400 mm, grey

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Maii: office@safetynet365.com Web: www.safetynet365.com









Available Colors grey Material high tenacity polypropylene, knotiless, polyamide screw-on brackets Material Diameter 22.5 mm Mesh Size 40 x 40 mm Pose of Meshes hombic (diamond mesh) Edge Design dijustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, holyseter cover), threaded all the way round Certificate Oko-Tex® certificate 1904052 Continuous Operating Temperature 40 to +80 °C Washing Temperature (max.) 30 °C Van Moisture Regain 90 °C Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Aklatis good/not good Resistance to Organic Solvents good Beding Strength & Abrasion Resistance good Weather-Resistance good Beding Strength & Abrasion Resistance good Beding Strength After Two Years of Climatic Influences 90 Besistance to Benzine and Greases good Beding Strength After Two Years of Climatic Influences good long-term flexibility, little elongation Possibility When Used in Water good long-term flexibility, little elongation	TECHNICAL DATA	
Material Diameter	Available Colors	grey
Mesh Size 40 x 40 mm Pose of Meshes rhombic (diamond mesh) Mesh Connection knottess braid Edge Design adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature 40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 9% Tensile Strength Reduction Because Of Moisture 9% Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good/not good Resistance to Organic Solvents 9cood/solvents 9	Material	high tenacity polypropylene, knotless, polyamide screw-on brackets
Pose of Meshes fhombic (diamond mesh) Mesh Connection knotless braid Adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature 40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Material Diameter	Ø 2.5 mm
Mesh Connection knotless braid Edge Design adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature -40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences 90% Elsticity After Years of Climatic Influences good long-term flexibility, little elongation	Mesh Size	40 x 40 mm
Edge Design adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature 40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Bending Strength & Abrasion Resistance good Weather-Resistance Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Pose of Meshes	rhombic (diamond mesh)
Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature -40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences 90% Elasticity After Years of Climatic Influences good long-term flexibility, little elongation	Mesh Connection	knotless braid
Certificate Oeko-Tex® certificate 1904052 Continuous Operating Temperature -40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Edge Design	adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core,
Continuous Operating Temperature -40 to +80 °C Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation		polyester cover), threaded all the way round
Melting Point 165 °C Washing Temperature (max.) 30 °C Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Certificate	Oeko-Tex® certificate 1904052
Washing Temperature (max.) Yarn Moisture Regain O% Resistance to Weak/Strong Acids Resistance to Weak/Strong Alkalis Resistance to Organic Solvents Resistance to Benzine and Greases Weather-Resistance Weather-Resistance Sood Weather-Resistance Bending Strength & Abrasion Resistance Sood Weather-Resistance Sood Bending Strength After Two Years of Climatic Influences Bending Strength After Two Years of Climatic Influences Sood Institute elongation	Continuous Operating Temperature	-40 to +80 °C
Yarn Moisture Regain 0% Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Melting Point	165 °C
Tensile Strength Reduction Because Of Moisture 0% Resistance to Weak/Strong Acids very good/good Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Washing Temperature (max.)	30 °C
Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Yarn Moisture Regain	0%
Resistance to Weak/Strong Alkalis good/not good Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Tensile Strength Reduction Because Of Moisture	0%
Resistance to Organic Solvents good Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Resistance to Weak/Strong Acids	very good/good
Resistance to Benzine and Greases very good Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences good long-term flexibility, little elongation	Resistance to Weak/Strong Alkalis	good/not good
Bending Strength & Abrasion Resistance good Weather-Resistance good Tensile Strength After Two Years of Climatic Influences 90% Elasticity After Years of Climatic Influences good long-term flexibility, little elongation	Resistance to Organic Solvents	good
Weather-Resistance good Tensile Strength After Two Years of Climatic Influences 90% Elasticity After Years of Climatic Influences good long-term flexibility, little elongation	Resistance to Benzine and Greases	very good
Tensile Strength After Two Years of Climatic Influences 90% Elasticity After Years of Climatic Influences good long-term flexibility, little elongation	Bending Strength & Abrasion Resistance	good
Elasticity After Years of Climatic Influences good long-term flexibility, little elongation	Weather-Resistance	good
	Tensile Strength After Two Years of Climatic Influences	90%
Flexibility When Used in Water stays flexible	Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
	Flexibility When Used in Water	stays flexible

Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Included Parts	luggage net, rubber cord, 4 or 5 screw-on brackets (depending on size), fastener for rubber cord
Customs Tariff No.	56081930
Total Weight	0.06 kg