


Product Data Sheet Item No. SN-016610-020

Elastic Storage Net, flexible

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 436 96 40
Mail: office@safetynet365.com
Web: www.safetynet365.com



**STANDARD
100**
12.0.02466
Hohenstein HTTI



TECHNICAL DATA

Material	polyester, knotless, flexible, with internal elasticated yarn, polyamide screw-on brackets
Material Diameter	Ø 2.5 mm
Mesh Size	20 x 20 mm
Pose of Meshs	rhombic (diamond mesh)
Mesh Connection	knotless braid
Edge Design	adjustable screw-on brackets with screw holes (Ø 4 mm), shock cord (Ø 5 mm, latex core, polyester cover), threaded all the way round
Certificate	Oeko-Tex®; certificate 1904052
Continuous Operating Temperature	-40 to +100 °C
Melting Point	260 °C
Yarn Moisture Regain	0.5 to 2.0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalis	good/good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	good
Bending Strength & Abrasion Resistance	good
Weather-Resistance	good
Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction

Behavior in High Heat / Fire	melting
Included Parts	luggage net, rubber cord, 4 or 5 screw-on brackets (depending on size), fastener for rubber cord, comes with an additional hook for the 1000 mm variant
Customs Tariff No.	56081930
Total Weight	0.00 kg