

Product Data Sheet Item No. SN-01650-010

Velcro Storage Net

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 436 96 40
Mail: office@safetynet365.com
Web: www.safetynet365.com



**STANDARD
100**
12.0.02466
Hohenstein HTTI



TECHNICAL DATA

| | |
|---|--|
| Dimensions | 140 x 330 mm, 190 x 360 mm |
| Material | polyester, knotless |
| Material Diameter | Ø 1.8 mm |
| Mesh Size | 10 x 10 mm |
| Pose of Meshes | rhombic (diamond mesh) |
| Mesh Connection | knotless braid |
| Edge Design | Velcro hook tape on both short sides, edged with textile tape (approx. 20 mm), sewn elastic rope on the upper edge |
| Certificate | Oeko-Tex®; certificate 1904052 |
| Continuous Operating Temperature | -40 to +100 °C |
| Melting Point | 260 °C |
| Yarn Moisture Regain | 0.5 to 2.0% |
| Tensile Strength Reduction Because Of Moisture | 0% |
| Resistance to Weak/Strong Acids | good/not good |
| Resistance to Weak/Strong Alkalis | good/good |
| Resistance to Organic Solvents | good |
| Resistance to Benzine and Greases | good |
| Bending Strength & Abrasion Resistance | good |
| Weather-Resistance | good |
| Tensile Strength After Two Years of Climatic Influences | 90% |
| Elasticity After Years of Climatic Influences | good long-term flexibility, little elongation |
| Flexibility When Used in Water | stays flexible |
| Contraction When Used in Water | low contraction |

| | |
|-------------------------------|----------------|
| Contraction When Used Outside | no contraction |
| Behavior in High Heat / Fire | melting |
| Customs Tariff No. | 56081930 |
| Total Weight | 0.00 kg |