


Product Data Sheet Item No. 2060-100-02

Lifting Net 4.00 x 4.00 m

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 819 818
Mail: office@safetynet365.com
Web: www.safetynet365.com



TECHNICAL SPECIFICATIONS

Available Colors:	white
Dimensions:	4.00 x 4.00 m
Material:	high tenacity polypropylene, knotless
Material Diameter:	Ø 6.0 mm
Mesh Size:	100 x 100 mm
Pose of Meshes:	quadratic (square)
Mesh Connection:	knotless braid
Edge Design:	reinforced selvage cord of approx. 9 mm, with edged rope, with two cross ropes through the net (PA Ø 14 mm), incl. loops with scuff protection on the corners
Edged Rope:	nylon rope (Ø 14 mm, white), all around
Max. Tensile Strength of a Mesh:	4200 N
Payload:	2 tons
Standards and Rules:	EN 1263-1
Certificate:	Oeko-Tex® certificate 12.0.02466
Continuous Operating Temperature:	-40 to +80 °C
Melting Point:	165 °C
Yarn Moisture Regain:	0%
Resistance to Weak/Strong Acids:	very good/good
Resistance to Weak/Strong Alkalis:	good/bad
Resistance to Organic Solvents:	good
Resistance to Benzine and Greases:	very good
Bending Strength & Abrasion Resistance:	good
Weather-Resistance:	good
UV-Resistance:	300 kly
Tensile Strength After Two Years of Climatic Influences:	90%
Customs Tariff No.:	56081930
Weight per Unit Area:	360 g/m ²
Total Weight:	11,20 kg