Product Data Sheet Item No. 7221-015

Air-Permeable Container Cover Sheet 3.00 x 5.00 m

Schutznetze24 GmbH Weyerberg 5, DE-35614 Aßlar-Berghausen Phone: +49 (0) 6443 - 436 96 40 Maii: office@safetynet365.com Web: www.safetynet365.com





TECHNICAL DATA

Resistance to Weak/Strong Alkalis

Resistance to Benzine and Greases

Bending Strength & Abrasion Resistance

Elasticity After Years of Climatic Influences

Resistance to Organic Solvents

Weather-Resistance

UV-Resistance

Available Colors



Dimensions	3.00 x 5.00 m
Material	polyethylene
Type of Textile	closemesh fabric panels, air and water permeable
Mesh Size	1 x 3 mm
Shading	50%
Edge Design	with reinforced and stitched edges all around (approx. 40 mm wide)
Eyelets	inside diameter Ø 16 mm, all around, with chosen spacing (standard every 50 cm)
Breaking Force	60 daN (according to DIN 53 857/1, average lengthways)
Breaking Elongation of Filament	15%
Standards and Rules	VDI standard 2700
Continuous Operating Temperature	-30 to +60 °C
Melting Point	155 °C
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	very good/good

dark green

good/good

very good

good

good

good

250 kly

90%

good long-term flexibility, no elongation

Tensile Strength After Two Years of Climatic Influences

Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	low contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Customs Tariff No.	63079010
Area Density	200 g/m²
Total Weight	3.98 kg