

Product Data Sheet Item No. 720
Windscreen Net by the m² (Custom-Made)

Schutznetze24 GmbH
 Weyerberg 5, DE-35614 Aßlar-Berghausen
 Phone: +49 (0) 6443 - 819 818
 Mail: office@safetynet365.com
 Web: www.safetynet365.com



Selectable Options:

Eyelet Spacing:

- approx. every 25 cm
- approx. every 30 cm
- approx. every 40 cm
- approx. every 50 cm
- approx. every 100 cm
- only at the corners
- without eyelets



TECHNICAL SPECIFICATIONS

Dimensions:	custom-made width, custom-made length
Available Colors:	dark green, light green, white, orange, blue, silver, terracotta, black
Material:	polyethylene
Type of Textile:	closemesh fabric panels, air and water permeable
Mesh Size:	1 x 3 mm
Production Tolerance:	external dimensions: ± 2.5 cm
Shading:	50%
Edge Design:	with reinforced and stitched edges all around (approx. 40 mm wide)
Eyelets:	inside diameter Ø 16 mm, all around, with chosen spacing (standard every 50 cm), (brass eyelets with orange, terracotta and cream version, stainless steel eyelets with all the other versions)
Breaking Force:	60 daN (according to DIN 53 857/1, average lengthways)
Continuous Operating Temperature:	-30 to +60 °C
Melting Point:	155 °C
Yarn Moisture Regain:	0%
Tensile Strength Reduction Because Of Moisture:	0%
Resistance to Weak/Strong Acids:	very good/good
Resistance to Weak/Strong Alkalis:	good/good
Resistance to Organic Solvents:	good
Resistance to Benzine and Greases:	very good
Bending Strength & Abrasion Resistance:	good
Weather-Resistance:	good
UV-Resistance:	250 kly
Tensile Strength After Two Years of Climatic Influences:	90%
Customs Tariff No.:	63079010
Weight per Unit Area:	200 g/m ²