

Product Data Sheet Item No. 59350K-320-01

Belt Strap Cargo Net For Cars 925 x 1825 mm - Complete Set

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 436 96 40
Mail: office@safetynet365.com
Web: www.safetynet365.com



TECHNICAL DATA

Available Colors	orange
Dimensions	925 x 1825 mm
Material	high tenacity polypropylene, knotless, polyester
Material Diameter	Ø 2.3 mm (cover net)
Strap Width	25 mm
Mesh Size	20 x 20 mm, 300 x 300 mm
Pose of Meshs	quadratic (square)
Mesh Connection	seamed
Edge Design	with edged polyester tape (approx. 25 mm wide), with D rings
Eyelets	D rings out of steel, directly sewn to the strap, diameter approx. 55 mm, in webbing loop, adds in total approx. 70 mm
Permissible Tensile Force	350 daN (lashing point), 1300 daN (net total)
Breaking Elongation of Filament	10%
Standards and Rules	EN 12195-2
Continuous Operating Temperature	-40 to +80 °C
Melting Point	165 °C
Washing Temperature (max.)	30 °C
Yarn Moisture Regain	0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	very good/good
Resistance to Weak/Strong Alkalis	good/not good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	very good
Bending Strength & Abrasion Resistance	good

Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Included Parts	cargo net incl. 4 tension belts (one-piece load restraint assembly, max. tensile force: 350 daN, length: 2.00 m)
Customs Tariff No.	63079010
Total Weight	2.25 kg