


Product Data Sheet Item No. 59400-150-04
Belt Strap Cargo Net 1525 x 4825 mm -
Complete Set

Schutznetze24 GmbH
Weyerberg 5, DE-35614 Aßlar-Berghausen
Phone: +49 (0) 6443 - 436 96 40
Mail: office@safetynet365.com
Web: www.safetynet365.com



TECHNICAL DATA

Available Colors	orange
Dimensions	1525 x 4825 mm
Material	polyester
Strap Width	25 mm
Mesh Size	150 x 150 mm
Pose of Meshes	quadratic (square)
Mesh Connection	seamed
Edge Design	with D rings
Eyelets	steel D rings (inner diameter approx. 30x35 mm, 6 mm strong), in webbing loop, adds in total approx. 60 mm
Permissible Tensile Force	400 daN (lashing point), 1300 daN (net total)
Breaking Elongation of Filament	10%
Standards and Rules	EN 12195-2, VDI standard 2700
Certificate	GS verification certificate
Continuous Operating Temperature	-40 to +100 °C
Melting Point	260 °C
Washing Temperature (max.)	90 °C
Yarn Moisture Regain	0.5 to 2.0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalis	good/good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	good
Bending Strength & Abrasion Resistance	good

Tensile Strength After Two Years of Climatic Influences	90%
Elasticity After Years of Climatic Influences	good long-term flexibility, little elongation
Flexibility When Used in Water	stays flexible
Contraction When Used in Water	low contraction
Contraction When Used Outside	no contraction
Behavior in High Heat / Fire	melting
Electrical Characteristics	isolating, no electrical conductivity
Included Parts	cargo net incl. 6 tension belts (two-piece load restraint assembly, max. tensile force: 1000 daN, length: 2.00 m)
Customs Tariff No.	63079010
Total Weight	6.50 kg