


Product Data Sheet Item No. 4516-350
Horizontal Climbing Net with Stainless Steel
Clamps by the m²

Schutznetze24 GmbH
 Weyerberg 5, DE-35614 Aßlar-Berghausen
 Phone: +49 (0) 6443 - 436 96 40
 Mail: office@safetynet365.com
 Web: www.safetynet365.com



TECHNICAL DATA

Available Colors	green, turquoise, orange, orange, fluorescent, blue, yellow, black, grey, red, fuchsia, beige (hemp colored), red/green/yellow/blue
Material	hercules rope [6 steel cables (Ø 2.4 mm), covered with polyester (Ø 5.4 mm), polypropylene core (Ø 8.3 mm)], cut resistant
Material Diameter	Ø 16.0 mm
Mesh Size	350 x 350 mm
Pose of Meshes	quadratic (square)
Mesh Connection	stainless steel clips
Edge Design	pressure-grouted or screwed fastening equipment according to choice
Breaking Force	minimum breaking force of rope: 42.0 kN, nominal tensile strength: 16 N/mm ²
Standards and Rules	EN 1176
Continuous Operating Temperature	-40 to +100 °C
Melting Point	260 °C
Yarn Moisture Regain	0.5 to 2.0%
Tensile Strength Reduction Because Of Moisture	0%
Resistance to Weak/Strong Acids	good/not good
Resistance to Weak/Strong Alkalis	good/good
Resistance to Organic Solvents	good
Resistance to Benzine and Greases	good
Bending Strength & Abrasion Resistance	good
Weather-Resistance	good
UV-Resistance	250 kly
Tensile Strength After Two Years of Climatic Influences	90%
Electrical Characteristics	isolating coating, electrically conducting core

Impregnation

acrylic resin polymer dispersion

Customs Tariff No.

95069990